## **CRYSOUND**

## **CRY577 Bluetooth Dongle**

The CRY577 Bluetooth Dongle is a Bluetooth device designed for Bluetooth audio and UI testing. It supports a variety of codecs and Hi-Res testing. It is suitable for R&D laboratories and production line testing. It can be used with the CRY6151B electroacoustic tester or as a separate module with other testing devices.CRY577 has strong reliability and fast test speed. The bluetooth connection with most solutions is less than 3 seconds. Users can cooperate with the CRY6151B test software or independent tool software to control the CRY577 Bluetooth Dongle to search, pair, connect, play audio and record.



## **Product features**

- √ High connection test efficiency
- ✓ Support Hi-Res certification test, LHDC/LDAC
- ✓ Supports basic information reading of Bluetooth devices
- ✓ Support SPP communication
- ✓ Support HID communication mode
- ✓ Support key tests such as music up and down, volume adjustment, pause / answer, etc
- ✓ Support recording, playback, listening and other tests
- ✓ Support DFU upgrade firmware



## **Bluetooth parameters**

Bluetooth version	5.0
Bluetooth protocol version	A2DP Source v1.3
	HFP Audio Gateway v1.7
	AVRCP Target v1.6
A2DP encoder	SBC
	aptX
	aptX HD
	LHDC (Hi-Res)
	LDAC (Hi-Res)
HFP codec	mSBC
	CVSD
A2DP sampling rate	96kHz, 88.2kHz, 48kHz, 44.1kHz
USB Interface	USB Type C
RF interface	SMA
Communication mode	USB HID
Appearance dimension	121mm*95mm*43mm (Without antenna)