



# CRY2620 Acoustic Imaging Camera

## Introduction

CRY2620 is a handheld industrial acoustic imager that supports the ultrasonic frequency range. The device uses microphone array beamforming technology to capture sound source distribution data.

CRY2620 industrial acoustic imager helps you quickly detect potential pressurized gas and vacuum leaks, even in noisy industrial environments.

CRY2620 is easy and intuitive to operate, allowing quick deployment. It supports both photo and video modes for flexible data recording in the field.

## Features

- Gas and Vacuum Leak Detection and Leak Rating Assessment
- Real-time Measurement and Display of Acoustic Data
- Rugged and Durable Design and Materials
- Generate Reports to Share Key Data

## Highlights

- **High-performance Microphone Array**  
Utilizing cutting-edge technology, it features a 12 cm diameter, 64-channel microphone array combined with beamforming technology to precisely locate sound sources.
- **High Efficiency, High Precision, and Long Testing Range**  
At a detection distance of 1 meter, the positioning error is within  $\pm 3$  mm, with a maximum testing range of up to 70 meters.
- **Gas/Vacuum Leak Detection & Leak Rating**  
Using advanced acoustic imaging technology, CRY2620 can quickly detect leaked gases and accurately locate the leak source. CRY2620 is also capable of quantifying the amount of leakage, enabling precise assessment of the economic losses caused by gas leaks.
- **Detects Leaks of Any Type of Gas**  
The CRY2620 is engineered to detect leaks of any gas type, offering exceptional versatility for a range of industrial applications. Employing advanced acoustic technology, the camera captures ultrasound waves emitted by gas leaks, regardless of the gas composition.
- **Robust and Durable, Suitable for Harsh Industrial Environments**  
Utilizes an aluminum alloy material with a sturdy structure that can withstand pressure, falls, and other impacts, guaranteeing stable operation in demanding environments.
- **IP54 Rating**  
IP54 rating, effectively preventing dust ingress and water splashing, making it suitable for complex environments.

## Technical Specifications

### Acoustic Specifications

Microphone Array	64 channels MEMS microphone
Frequency Range	2 kHz - 40 kHz
Dynamic Range	0.5 dB - 12 dB user adjustable
Test Sound Pressure Level Range	28 - 120 dBA
Test Distance	0.5 - 70 m
Leak Detection Rate	10 m 5 bar 144 ml/min 0.5 m 5 bar 72 ml/min

### Camera

FOV	62°
Focal Length	3.04 mm
Camera Pixels	8M pixels

### Display

Resolution	1024 × 600 (614,400 pixels)
Size	7 inch
Touch Screen	Capacitive touch screen
Brightness	Adjustable

### Storage

Storage Size	8G internal, 64G external
Storage Format	.jpg (Photo), .mp4 (video), .wav (audio)

### General Specifications

Size	272 × 174 × 42 mm
Weight	1.7 kg
IP Rating	IP54
System	Linux system
Operating Environment	-20°C to +50°C, 10% to 95% no cond.
Storage Temperature	-20°C to +60°C

### Certifications

Certifications	CE-EMC, CE-ROHS, FCC, PSE
----------------	---------------------------

### Software

Function	Multi-point imaging, directional focus, distance measurement, leak volume estimation, PRPD spectrum, type recognition, picture labelling, report export, and etc.
----------	---

### Port

USB-C	USB 3.0
3.5mm Audio Jack	Headphone output
MicroSD Card Slot	External storage

## Ordering Information

Name	Model	Describe
Acoustic Imaging Camera	CRY2623	Detect non-explosive gas leaks and partial discharge.
ATEX Acoustic Imaging Camera	CRY2624	ATEX-certified
Acoustic Imaging Camera	CRY8124	Detect non-explosive gas leaks and partial discharge.
EX Acoustic Imaging Camera	CRY8125	IECEX and ATEX certified
Ultrasound Generator	IA1101	Simulate gas leaks or partial discharge for system calibration.
Thermal Imaging Camera Module	IA1301/1302	Optional accessory: Resolutions of 384 × 288 and 640 × 512 are available.
Smart Battery Pack	IA2001	Optional accessory: Single battery provides 5h operation.

